


C2C-6C



CEILING MOUNT IP SPEAKER

Click2Connect Indoor Ceiling Mount IP Speaker is a steadfast and high endurance SIP enabled speaker that can be used for multiple applications such as broadcasting prerecorded messages, important notifications and alerts, scheduled announcements, SIP paging, streaming high-def playback music etc. Our range of IP Speakers is a real innovation in design and performance. These exceptional speakers are both stylish and elegant and offer a cost effective and robust solution.

Application Scenarios



Park



Campus



Shopping Centers



Train/Bus Stations



Airports



Schools



Residential Buildings



Retail Shops



Restaurants



Office Buildings



Warehouses



Hotels



Features



**Reliable
IP Ceiling Speaker
with Crystal clear
HD Sound Clarity**



AC POWERED

**Direct Connect
AC 220V**



**Quick and Easy
Installation on Single
Network Cable**



**Built in
Class D
Amplifier**



**Self Test Function
for
Device Status**



**Master report
function
(*Excel, Pdf)**



**Remotely speaker
firmware upgradation
through
Click2Connect Server**



**Remote Health
Status of
Speaker**



**Remotely Volume
Control**



**Any IP Camera
Can integrate
and
Bind with Speakers**



**Easy
integration with
any VMS**



**E-Mail
and SMS
alerts**



Schematic Diagram

*Click2Connect
IP Audio Gateway Embedded with Software*

Click2Connect MOBILE & Desktop APP

Wall Mount IP Speakers



Network Cable



Switch

IP Ceiling Speakers



Network Cable

IP Horn speakers



Network Cable

IP Horn speakers



Network Cable



Network Cable



Switch



Network Cable



Switch

Network Cable / Fiber optic Cable

Network Cable / Fiber optic Cable

Specifications:

Speaker	
Input Power	6W RMS/9W Max.
SPL at 1 kHz (1W/1m)	4Ω
Amplifier	Built-in Class D Amplifier
Effective frequency range(-10dB)	80 Hz to 18 kHz
SPL at 1kHz	94 dB / 86 dB (SPL)
Dimensions	Ø 199 mm
Audio	
Audio codecs:	G.722, G.711 A-law, G.711 U-law, Opus
Audio streaming:	MP3 sampling rate 8 – 48KHz, bit rate 64 – 320kbps, mono or Stereo
Network	
Interface:	RJ45 10/100
Protocols:	SIP(RFC3261), HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH
Administration	
Configuration:	By Click2Connect Server
Environmental	
Installation environment:	Indoor
Operating temperature:	-10°C - 70°C
Connection Diagram	

CEILING MOUNT IP SPEAKER

